



Leitor Argox AI-6821

O Leitor Argox AI-6821 é o primeiro modelo de scanner sem fio da Argox, indicado especialmente para indústrias de pequeno à médio porte. Sua taxa de transmissão é 3 vezes mais rápida do que os modelos da categoria.

EAGLE EYE Series

AI-6821

Wireless 2D Barcode Imager



Outstanding Scanning Performance

Based on the outstanding reading performance 2D CMOS imager scan engine, AI-6821 is the first Argox wireless light-industry grade 2D scanner. With enhanced reading capability on 4 mil labels for components and jewelry labels, AI-6821 has been well recognized by Argox customer groups for its snappy readings and rigid structures in light industrial applications.

User Friendly Aiming Light

Built-in laser cross aimer of AI-6821 made it easy for user to aim the reading target under strong or with very low ambient light source.

Superb Wireless Data Transmission

With Class-1 Bluetooth module built in, AI-6821 can transmit scanned data to receiver within 100-meter range. For warehouse and logistic operations, AI-6821 can provide services non-stop over the whole working shift.

In Store or On the Floor Use

AI-6821 can be perfect scanning device for inventory check. For factory shop floor use, AI-6821 can be great helping hands with built in vibrator for good-read and data receiving acknowledge indicator.

Built to Survive Harsh Environment

IP65 structure design of AI-6821 makes it survive multiple 1.8-meter drop on concrete. No moving parts inside of AI-6821 outperforms laser scanner in various applications in factory and warehouse.

Versatile Data Editing to Adopt Database Format

AI-6821 comes with powerful DataMagic data editing tool. It allows AI-6821 to transmit scanned data after been edited according to preset rules to fit in specific database format. No matter it is for special data length, special truncation, special re-organization of the data sequence, even replacing specific data with designated numbers or characters. Substantial efforts used to be required after data scanning can now all be eliminated through simple setting on screen via friendly user interface then download into AI-6821.



Application:

- Retail
- Healthcare
- Warehouse
- Transportation & Logistic
- Manufacturing



Cradle- Features:

Smart Cradle

1. User friendly cable alignment groove for different desktop positioning.
2. U-Shape LED indicator provides clear scanner status indication even from far.
3. Multi-function cradle: Data receiving/transmission, scanner charging, and firmware upgrade.



Model	AI-6821		AI-6821HD	
PERFORMANCE CHARACTERISTICS				
Scan Pattern	Area Imager (752x480 pixel array)			
Light source	Aiming Pattern: 655 +/- 10 nm laser diode Illumination: 625 +/- 5 nm LED			
Field of View	39.6° horizontal, 25.7° vertical			
Roll/Pitch/Skew	360°, ±60°, ±60°			
PHYSICAL CHARACTERISTICS				
Dimensions	Scanner 9.4x 7.6x15.8 cm		Cradle:13x8.8x9.5 cm	
Weight	Scanner :200g (Battery included) Cradle:130g			
Indicator	LED , beeper, vibrator			
Resolution	1D (4 mil): Code 39 2D (6.7 mil): PDF417		1D (3 mil): Code 39 2D (4 mil): PDF417	
SYMBOLLOGY DECODE CAPABILITY				
1-D Symbolologies	UPC/EAN (UPCA/UPCE/UPCE1/EAN-8/EAN-13/JAN-8/JAN13 plus supplementals, ISBN (Bookland), ISSN, Coupon Code, Code39 (Standard, Full ASCII, UCC/EAN-128,ISBT-128 Concatenated), Code 93, Codabar/NW7, Code 11 (standard, Matrix 2 of 5),MSI Plessey, I2 of 5 (Interleaved 2 of 5 / ITF, Discrete 2 of 5 IATA, Chinese 2 of 5), GS1 Databar (Omnidirectional, Truncated,Stacked, Stacked Omnidirectional, Limited, Expanded, Expanded Stacked, Inverse), Base 32 (Italian Pharmacode)			
PDF417 (and Variants)	PDF417, microPDF417, Composite Codes (OCR-A, OCR-B)			
2-D Symbolologies	TLC-39, Aztec (Standard, Inverse), MaxiCode, DataMatrix/ECC 200 (Standard, Inverse), QR Code (Standard, Inverse and Micro)			
Print Contrast	25% minimum reflectance			
Interface Supported	RS-232 , USB			
Depth of Field	Code39 5mil 100% UPC Datamatrix 15 mil QR Code 8 mil QR Code 20 mil PDF417 13 mil	42~143mm 37~358mm 32~280mm 67~110mm 37~320mm 22~250mm	Code39 3mil Code39 5mil UPC 13mil QR Code 8 mil QR Code 20 mil PDF417 13 mil	25~75mm 25~105mm 45~150mm 30~80mm 35~160mm 25~115mm
USER ENVIRONMENT				
Operating Temperature	-20°C to 55°C (-4°F to 131°F) (Charging 0~40°C)			
Storage Temperature	-20°C to 70°C (-4°F to 158°F)			
Humidity	5% to 95% related humidity, non-condensing			
Drop Specifications	Withstands multiple 6 ft./1.8 m drops to concrete			
Contaminants	Seals to resist airborne particulate contaminants (IP65)			
Ambient Light Immunity	Up to 100,000 LUX, Immune to normal artificial indoor and natural outdoor (direct sunlight) lighting			
REGULATORY				
Electrical Safety	EN60950-1, CNS14336,			
Laser Safety	EN60825-1:1994 +A1: 2002 +A2 2001, IEC60825-1, 21CFR1040.10 and 21CFR1040.11, CDRH Class II, IEC Class 2			
EMI/RFI	CE, FCC, BSMI, NCC			
Environmental	Compliant with RoHS directive 2002/95/EEC			
Radio	Bluetooth™, Class 1(100M, in open area), Version 2.1 + EDR, Data rate — up to 3 Megabits/sec			
ACCESSORIES				
Power Supplies	Power supplies are available to support faster charging or USB cable			
ELECTRICAL CHARACTERISTICS				
Battery	Rechargeable Li-Ion battery pack (3.7V, 2200mAh, 9.25Wh)			
Battery Charger Time	Power adapter : 4.5 hours USB cable : 6.5 hours			
Power Input	5V ± 10% VDC / 1A			

*Argox reserves the right to enhance and modify the specification without prior notice.
Please check Argox sales representative for most updated specifications.

Argox Information Co., Ltd.

7F., No.126, Ln.235, Baoqiao Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)
Tel: +886-2-8912-1121 Fax: +886-2-8912-1124 <http://www.argox.com> <https://www.youtube.com/user/argoxmkt> email:service@argox.com
Copyright © 2017. Argox Information Co., Ltd. All Rights Reserved.

