



Computador All in One Bematech SB-9015F

O SB-9015F é o novo lançamento da Bematech. Criado para tornar o atendimento aos clientes mais ágil e intuitivo. Unindo em um único equipamento um monitor touch screen de 15 polegadas com um computador de alto desempenho na medida certa para o seu negócio.

www.bztech.com.br



Features

- Supports a wide range of operating systems
- Flexible configurations available
- Easy to change or replace HDD
- Cable management compartment
- Easy access to system core for maintenance
- Optional MSR and customer display (line display or LCD) available

SB9015F



Dual-core All in One Terminal

SB9015F delivers the perfect blend of quality, performance, durability, and economy that make it the Best-in-Class hardware for Point-of-Sale All in One touch screen systems. The SB9015F is equipped with an industrial computer core and can support a wide range of operating systems. It is a perfect choice when an All In One solution is needed. Just one thumb-screw located at the back panel of the monitor allow an easy access to the computer core for service and maintenance.



SB9015F SPECIFICATIONS

MAINBOARD

CPU Intel Atom Processor,
D525 dual core 1.8GHz

STORAGE DEVICES

HDD SATA 2.5" HDD, 160GB or higher

SYSTEM MEMORY 2 slots, DDR3 1066/1333, up to 4GB

DISPLAY

Panel LCD 15" TFT LCD
Brightness 250cd/m2
Resolution 1024 x 768
Touch Screen 5- wire Resistive Type
(RS232 interface)

MECHANICAL

Dimensions 13" x 13.7" x 8.4"
(L x W x H)
Weight 22.04 lbs
Temperature Operating: 0°C – 40°C
Storage: -25°C to 70°C
Relative Humidity 8% – 80%, non-condensing

I/O PORTS

Serial 3 x DB9 with DC5V/12V on pin 9
(jumper optional) 1xRJ45
External DC Input 1 x DC jack (connected to power adapter)
DC Output 1 x DC 12V output
Parallel Optional 1xDB25 on cable
USB 6 x USB 2.0
PS/2 1 x PS/2 keyboard
LAN 1 x RJ-45, 1/100M/1Gbit
Cash Drawer Port 1 x RJ-11, 12V/24V jumper selectable
Audio 1 x Audio out, 2x 1W built-in speaker
VGA 1 x DB15 2nd video VGA connector

ELECTRICAL

Input 100V a 240VAC, 50 a 60Hz, 2.0A
Output DC 24V 5A
Output Power 120 max

OS SUPPORT Windows XP, POS Ready 7, POS Ready 2009,
Windows 7

Certification FCC, CE

Options MSR / VFD / Second LCD Display

McNETIC LTDA.

Telefonos 359-41-63

Celular 315-3317328

Calle 20 No.82-52 Oficina 455

Centro Empresarial Hayuelos



McNETIC

Negocios Estratégicos de Tecnología Informática de Colombia


bematech

www.bematech.com