



## Computador All in One Bematech SB-9015F

O SB-9015F é o novo lançamento da Bematech. Criado para tornar o atendimento aos clientes mais ágil e intuitivo. Unindo em um único equipamento um monitor touch screen de 15 polegadas com um computador de alto desempenho na medida certa para o seu negócio.



### Features

- Supports a wide range of operating systems
- Flexible configurations available
- Easy to change or replace HDD
- Cable management compartment
- Easy access to system core for maintenance
- Optional MSR and customer display (line display or LCD) available

# SB9015F



## Dual-core All in One Terminal

SB9015F delivers the perfect blend of quality, performance, durability, and economy that make it the Best-in-Class hardware for Point-of-Sale All in One touch screen systems. The SB9015F is equipped with an industrial computer core and can support a wide range of operating systems. It is a perfect choice when an All In One solution is needed. Just one thumb-screw located at the back panel of the monitor allow an easy access to the computer core for service and maintenance.



# SB9015F SPECIFICATIONS

## MAINBOARD

CPU Intel Atom Processor,  
D525 dual core 1.8GHz

## STORAGE DEVICES

HDD SATA 2.5" HDD, 160GB or higher

**SYSTEM MEMORY** 2 slots, DDR3 1066/1333, up to 4GB

## DISPLAY

Panel LCD 15" TFT LCD  
Brightness 250cd/m2  
Resolution 1024 x 768  
Touch Screen 5- wire Resistive Type  
(RS232 interface)

## MECHANICAL

Dimensions 13" x 13.7" x 8.4"  
(L x W x H)  
Weight 22.04 lbs  
Temperature Operating: 0°C – 40°C  
Storage: -25°C to 70°C  
Relative Humidity 8% – 80%, non-condensing

## I/O PORTS

Serial 3 x DB9 with DC5V/12V on pin 9  
(jumper optional) 1xRJ45  
External DC Input 1 x DC jack (connected to power adapter)  
DC Output 1 x DC 12V output  
Parallel Optional 1xDB25 on cable  
USB 6 x USB 2.0  
PS/2 1 x PS/2 keyboard  
LAN 1 x RJ-45, 1/100M/1Gbit  
Cash Drawer Port 1 x RJ-11, 12V/24V jumper selectable  
Audio 1 x Audio out, 2x 1W built-in speaker  
VGA 1 x DB15 2nd video VGA connector

## ELECTRICAL

Input 100V a 240VAC, 50 a 60Hz, 2.0A  
Output DC 24V 5A  
Output Power 120 max

**OS SUPPORT** Windows XP, POS Ready 7, POS Ready 2009,  
Windows 7

Certification FCC, CE

Options MSR / VFD / Second LCD Display

McNETIC LTDA.

Telefonos 359-41-63

Celular 315-3317328

Calle 20 No.82-52 Oficina 455

Centro Empresarial Hayuelos



# McNETIC

Negocios Estratégicos de Tecnología Informática de Colombia

  
bematech

[www.bematech.com](http://www.bematech.com)