



## Monitor Elo 1537L

O monitor Elo Touch ET1537L é fabricado com materiais extremamente resistentes, possui vedação para suportar derramamentos de água, gordura e poeira, tudo isso para gerar um longo ciclo de vida, diminuindo tempo de inatividade e custos com manutenção.



# 1537L 15" LCD Open-Frame Touchmonitor

Space-saving design ideal for kiosk, gaming, and light industrial applications

**The Elo 1537L open-frame LCD touchmonitor** complements the Elo TouchSystems expanding family of touch solutions for kiosk information systems, gaming and amusement, and light industrial shop-floor automation. This compact touchmonitor is "designed for touch," with proven Elo expertise and reliability built in. An integrated precision mini-bezel seals the touchscreen against dirt, dust and liquids, which simplifies integration into the final enclosure. Long-lasting product availability can be expected as the design and tooling is controlled by Elo specifications, allowing future-generation panels to be phased in without external changes.

The 1537L is available with a choice of industry-leading Elo touch technologies: AccuTouch five-wire resistive, APR (acoustic pulse recognition), CarrollTouch infrared, IntelliTouch surface acoustic wave, SecureTouch vandal-resistant surface wave and surface capacitive. A dual serial/USB touch interface is available on most models, with only a USB interface on the APR monitor. Worldwide agency approvals cover the whole monitor, which is developed, built, serviced and supported by a true single-source supplier. The 1537L open-frame LCD touchmonitor provides an economical solution for system integrators and VARs.

## Benefits

- Elo reliability and quality at an economical price point
- "Designed for touch" from the ground up
- Choice of Elo touch technologies: AccuTouch, APR, CarrollTouch, IntelliTouch, SecureTouch and surface capacitive
- Touchscreen sealed against dirt, dust and liquids
- Compact and easy to integrate with mounting from sides or top and bottom; also a VESA mount option
- Dual serial/USB touch interface on most models; APR is USB only
- Worldwide agency approvals
- Three year standard warranty

## Applications

- Kiosk information systems
- Gaming and amusement
- Light industrial shop-floor automation



# 1537L 15" LCD Rear-Mount Touchmonitor Specifications

Case/Bezel color	Silver minibezel
Display type	Active matrix TFT LCD
Display size	15.0" diagonal
Aspect ratio	4 x 3
Useful screen area	Horizontal: 12" (304 mm); Vertical: 9" (228 mm)
Monitor dimensions	Width: 13.2" (336 mm) Height: 10.4" (264 mm) Depth: 1.6" (41 mm)
Dimensional drawing number	MS600159
Optimal (native) resolution	1024 x 768
Other supported resolutions	1024 x 768 at 60, 65 (Sun), 70, or 75 Hz; 832 x 624 at 75 Hz (Mac); 800 x 600 at 56, 60, 72, or 75 Hz; 720 x 400 at 70 Hz; 720 x 350 at 70 Hz; 640 x 480 at 60, 66 (Mac), 72, or 75 Hz
Colors	16.2 million colors with dithering
Brightness (typical)	LCD panel: 250 cd/m <sup>2</sup>
LCD panel with touchscreen (typical)	AccuTouch: 200 cd/m <sup>2</sup> Acoustic Pulse Recognition: 230 cd/m <sup>2</sup> CarrollTouch: 230 cd/m <sup>2</sup> Surface Capacitive: 213 cd/m <sup>2</sup>
Response time	14.5 msec (typical)
Viewing angle (from center)	Horizontal (left / right): 140° total; Vertical (up /down): 115° total
Contrast ratio (typical)	500:1
Input video format	RGB analog
Input sync format	Separate H & V sync, composite sync, and sync-on-green
Input video signal connector	Mini D-Sub 15-Pin VGA type
Scanning frequency	Horizontal: 31.5 - 60.2 kHz; Vertical: 56.3 - 75 Hz
Power dissipation	30 W max.
Power supply	Type: external brick; Input (line) voltage: 100-240 VAC, 50/60Hz; Monitor input voltage, current: +12 VDC +/- 5% at 2.5A maximum
Temperature	Operating: 0°C to 40°C; Storage: -20°C to 60°C
Humidity	Operating: 20% to 80% (non-condensing); Storage: 10% to 90% (non-condensing)
Backlight lamp life	Typical 30,000 hours to half brightness
Monitor MTBF (excluding lamps)	50,000 hours demonstrated
Weight (approx.)	Actual: 6.6 lbs (3.0 kg); Shipping: 9.7 lbs (4.4 kg)
Warranty	Touchmonitor: 3 years in U.S.
User's controls	OSD buttons: menu, up, down, select, power; OSD: contrast, brightness, H/V position, RGB (color temp), clock, phase, recall, language (English, German, Spanish, Japanese, French); OSD disable/enable: power, OSD menu
Mounting options	100 mm or 75 mm VESA mount; open-frame with brackets; mounting brackets included
Agency Certification	UL, cUL, FCC, CE, TÜV-GS, VCCI, IC, C-Tick

To find out more about Elo's extensive range of touch solutions, go to [www.elotouch.com](http://www.elotouch.com), or call the office nearest you.

## North America

800-ELO-TOUCH  
Elo TouchSystems  
301 Constitution Drive  
Menlo Park, CA 94025-1110  
Tel 1-650-361-4800  
Fax 1-650-361-4722  
customerservice@elotouch.com

## Europe

Tel +32 (0)16 35 21 00  
Fax +32 (0)16 35 21 01  
elosales@elotouch.com

## Asia-Pacific

Tel +81 (45) 478-2161  
Fax +81 (45) 478-2180  
www.tps.co.jp

## Latin America

Tel 786-923-0251  
Fax 305-931-0124  
www.elotouch.com.ar



Tyco Electronics reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.  
AccuTouch, Acoustic Pulse Recognition, Elo TouchSystems, IntelliTouch, TE Logo, and Tyco Electronics are trademarks.  
Copyright 2008 Tyco Electronics Corporation 6/08

