



## Monitor Elo 1937L

O Elo 1937L possui um painel moldado por injeção com uma vedação à prova d'água praticamente invisível, tornando-se assim uma boa escolha para suportar os rigores do uso público.



# 1937L 19" LCD Open-Frame Touchmonitor

High-quality panel and choice of touch technology in a compact form factor

**The 1937L open-frame touchmonitor delivers a cost-effective touch solution** for OEMs and systems integrators, and complements the expanded family of Elo touch solutions for gaming and amusement, retail self-service and kiosk applications. This compact touchmonitor is "designed for touch," with proven expertise and reliability built-in, not added as an afterthought by altering an existing monitor.

Like all Elo open-frame touchmonitors, the specifications and tooling are controlled to ensure a long product life, which is important in maintaining continuity for all phases of project rollouts and servicing. The 1937L features an injection-molded bezel with a virtually invisible watertight seal, thus making it a good choice to withstand the rigors of public use. Narrow borders, black anodized bezel hardware, multiple mounting options, and dual serial/USB touch interface (APR is USB only) add to the touchmonitor's flexibility. Worldwide agency approvals cover the entire monitor that is developed, built and supported by Elo TouchSystems, a true single-source supplier.

The 1937L is available with a choice of one of Elo's industry-leading touch technologies: Acoustic Pulse Recognition (APR), AccuTouch 5-wire resistive or IntelliTouch surface acoustic wave. The comprehensive range of features includes an analog interface, multi-lingual on-screen display (OSD), mounting VESA standard, mounting brackets, cabled remote on-screen display (OSD), and worldwide compliance.

## Features

- High quality panel with 160° x 160° viewing angle
- 800:1 contrast ratio
- Long-lasting product cycle—enclosure controlled by Elo specifications
- Future generation panels phased-in without external changes
- Integrated precision mini-bezel with watertight 0.5 mm seal
- Mounting options including rear-mount (with two included mounting brackets) and VESA mount
- Acoustic Pulse Recognition (APR) touch technology with USB interface; AccuTouch 5-wire resistive and IntelliTouch touch technologies with dual serial/USB touch interfaces
- Integrated multilingual on-screen display (OSD), connector for optional remote on-screen display (OSD)
- Worldwide agency approvals
- 3 year warranty
- 3D electronic design files available



# 1937L 19" LCD Open-Frame Touchmonitor Specifications

Case/Bezel color	Steel/black
Display	Size: 19.0" diagonal; Type: Active matrix TFT LCD; Aspect ratio: 5 x 4
Useful screen area	Horizontal: 14.8" (376 mm); Vertical 11.9" (301 mm)
Monitor dimensions	Width: 16.3" (415 mm); Height: 13.5" (343 mm); Depth: 2.0" (51 mm)
Optimal (native) resolution	1280 x 1024
Other supported resolutions	1280 x 1024 at 60, 70 or 75 Hz; 1280 x 960 at 60 Hz; 1152 x 864 at 75 Hz
Colors	16.7 million colors
Brightness (typical)	LCD panel: 250 nits; with AccuTouch: 200 nits; with Acoustic Pulse Recognition: 225 nits; with IntelliTouch: 225 nits
Response time (typical)	10 msec
Viewing angle (typical)	Horizontal: 160° total; Vertical: 155° total
Contrast ratio (typical)	800:1
Input video format	Analog VGA
Input video signal connector	Mini D-Sub 15-Pin VGA type
Input frequency	Horizontal: 31.5-80.0 kHz; Vertical: 56.3-75 Hz
Power supply	External DC—optional power brick (sold separately) Input voltage—DC: +12VDC ±5% Input power connector specification (monitor)—Type: DC Barrel Jack; Barrel inner diameter: 6.4 mm (±0.3 mm); Pin outer diameter: 2.0 mm (+0.0 -0.1 mm); Barrel depth: 8.8 mm (±0.3 mm) Power connector (power brick)—Type: DC Barrel Plug; Barrel outer diameter: 5.5 mm (±0.1 mm); Pin inner diameter: 2.1 mm (±0.1 mm); Barrel length: 9.5 mm (±0.5 mm)
Power consumption (typical)	Monitor: 38 W; Monitor and power brick: 43 W
Temperature	Operating: 0°C to 40°C (32°F to 104°F); Storage: -20°C to 60°C (-4°F to 140°F)
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-90%
Weight	Actual: 5.2 kg (11.5 lbs); Shipping: 7.3 kg (16.1 lbs)
Shipping box dimensions (W x D x H)	20.28" (515 mm) x 17.72" (450 mm) x 6.89" (175 mm)
Warranty	Touchmonitor: 3 years
Backlight lamp life (typical)	50,000 hours to half brightness
Mean time between failures (MTBF)	50,000 hours demonstrated
Agency approvals	UL, cUL (Recognized) , TUV-T Mark, Argentina S, CE, FCC, VCCI, IC, C-TICK (Class B), NOM, BSMI, KCC, CCC, China RoHS
On-screen display (OSD)	Controls (optional remote with 1.8m cable): Auto/Sel, up, down, menu Controls (back): menu, left, right, select, power Settings: contrast, brightness, H/V position, RGB (color temp), clock, phase, recall Languages: English, German, Spanish, Japanese, French Lockouts: power, user controls
Mounting options	75 mm or 100 mm VESA mount; Rear mount or with included standard mounting brackets; Front mount with optional bezel; Rack mount with optional bracket
Sealing	Touchscreen sealed to bezel; Touchscreen sealed to LCD

To find out more about our extensive range of Elo touch solutions, go to [www.elotouch.com](http://www.elotouch.com), or call the office nearest you.

Macroservice, S.A.  
C/General Margallo, 29 Local  
28020 Madrid - Spain



informacion@macroservice.es - [www.macroservice.es](http://www.macroservice.es)  
T. +34 (91) 571 52 00 - F. +34 (91) 571 19 11



Tyco Electronics Corporation and its Affiliates in the TE Touch Solutions business unit of the TE Connectivity Ltd. family of companies (collectively "TE") reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.  
AccuTouch, Elo (logo), Elo TouchSystems, IntelliTouch, TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks of the TE Connectivity Ltd. family of companies.  
Copyright 2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company. All rights reserved. 04/11

