



Computador EloTouch ECMG2

Elimine os excessos de fios e periféricos ligados a seus monitores, utilizando então o computador Elo ECMG2 que se acopla atrás dos monitores, deixando mais seguro e o ambiente mais limpo.

www.bztech.com.br

- Integrates touch computing with Interactive Digital Signage
- Intel Core i3/i5 processors running Microsoft Windows
- Platform for collaboration, digital whiteboard, building directory, virtual receptionist and other applications
- 3 year global warranty



ECMG2 Computer Modules for Interactive Digital Signage

The Elo Interactive Digital Signage (IDS) touch screen enables increased customer engagement and immersive brand experiences by adding an exciting new dimension to traditional broadcast digital signage – the power of touch. Elo’s ECMG2 computer modules, available for use with the Elo 3201L, 4201L, 5501L and 7001L IDS touchscreens are well-suited for interactive media delivery and online collaboration for modern office environments. Computer modules are available in a choice of two models: ECMG2-i3 based on a 3.3GHz Intel® Core i3 processor and HD2500 graphics; and ECMG2-i5 based on a 2.9GHz (3.6 GHz Max Turbo) Intel Core i5 processor and HD4000 graphics.

Centralized management and security capabilities of Microsoft® Windows® ensures compatibility with many content management servers and web-based consoles for seamless connection with the internet, digital marketing, interactive whiteboard, building directory, virtual receptionist, and point-of-information (POI) applications.

The ECMG2 computer modules can support optimal partitioning of locally cached and network stored content, allowing developers to monitor and deploy content via device-to-device or web connections.



Benefits:

- A fully self-contained computing solution when coupled with Elo IDS touch screens
- Professional-grade hardware provides improved durability
- Intel Core i3 and Core i5 with high-end graphics enable media-rich interactive experiences
- Quick-access hard drive for easy initial imaging and field service.
- Microsoft Windows platform offers maximum compatibility

About Elo

Elo founders pioneered the touch screen over 40 years ago. Today, Elo Touch Solutions is a leading global supplier of touch-enabled technology, products and industry solutions. The Elo portfolio encompasses the broadest selection of OEM touch screen components, touch monitors, and all-in-one touch computers for the demanding requirements of diverse markets, including gaming machines, hospitality systems, industrial automation, interactive kiosks, healthcare, office equipment, point of sale terminals, retail displays, and transportation applications. The Elo touch experience has consistently stood for quality, reliability and innovation with over 20 million installations worldwide.

ECMG2 Computer Modules for Interactive Digital Signage Touch Displays

Specifications			
Module Dimensions	Width: 10.8" (274 mm) Depth: 9.8" (248 mm) Height: 1.8" (45.7 mm)		
Processor	<table border="0"> <tr> <td>Intel Core i3 i3-3220 3.30 GHz 3MB Intel® Smart Cache 5 GT/s DMI</td> <td>Intel Core i5 i5-3475S 2.9GHz (3.6 GHz Max turbo) 6MB Intel® Smart Cache 5 GT/s DMI</td> </tr> </table>	Intel Core i3 i3-3220 3.30 GHz 3MB Intel® Smart Cache 5 GT/s DMI	Intel Core i5 i5-3475S 2.9GHz (3.6 GHz Max turbo) 6MB Intel® Smart Cache 5 GT/s DMI
Intel Core i3 i3-3220 3.30 GHz 3MB Intel® Smart Cache 5 GT/s DMI	Intel Core i5 i5-3475S 2.9GHz (3.6 GHz Max turbo) 6MB Intel® Smart Cache 5 GT/s DMI		
Chipset	Intel® H61 Express Chipset		
Video	i3 – Intel® HD 2500 i5 – Intel® HD 4000		
BIOS	AMI		
Memory (RAM) Standard/max./slots	i3 – 2GB DDR3 SO-DIMM on 1 of 2 slots i5 – 4GB DDR3 SO-DIMM on 1 of 2 slots (Expandable up to 8GB MAX SO-DIMM DDR3-1333/1600 (PC3-10600))		
Hard Disk Drive	320GB 2.5" ADVANCED FORMAT (AF) SATA HDD		
Operating Systems Supported	No Operating System Microsoft Windows 7 Professional (32-bit) Microsoft Windows Embedded 8.1 Industry (64-bit)		
Languages	Windows 7/8.1: 35 language groups: Arabic, Brazilian Portuguese, Bulgarian, Chinese (Simplified), Chinese (Traditional), Chinese (Hong Kong), Croatian, Czech, Danish, Dutch, English, Estonian, Finnish, French, German, Greek, Hebrew, Hindi, Hungarian, Italian, Japanese, Korean, Lithuanian, Norwegian, Polish, Portuguese, Romanian, Russian, Serbian Latin, Slovak, Slovenian, Spanish, Swedish, Thai, Turkish, Ukrainian		
USB Port (s)	4 x Type A ports		
Ethernet Port(s)	1 x LAN RJ45 (Gigabit)		
Audio Port(s)	Microphone in, line out		
Rear I/O (Summary of all above ports)	4 Type A USB ports 1 Gigabit Ethernet LAN RJ45 port 3 3.5 mm TRS jacks for Audio In, Audio Out, Microphone in		
Real Time Clock	Replaceable lithium-ion battery for clock		
Power Supply	Power supplied by Interactive Digital Signage display		
Weight	Actual: 4.47 lb (2.03 Kg) Shipping: 6.4 lb (2.9 Kg)		
Shipping Box Dimensions	Width: 15.4" (392 mm) Depth: 14.25" (362 mm) Height: 5.1" (130 mm)		
Temperature	Operating : 0°C to 40°C (32°F to 104°F) Storage : -20°C to 60°C (-4°F to 140°F)		
Humidity (non-condensing)	Operating : 20% to 80% Storage : 5% to 95%		
Agency Approvals	US UL, FCC; Canada cUL, IC; Europe CE; Japan VCCI; Taiwan BSMI; Korea KC; International CB		
Warranty	3 years		
MTBF	50,000 hours demonstrated		

Ordering Information

Model	Part Number	Processor	RAM	HDD	OS
ECMG2-i3	E776797	Intel Core i3 3.3GHz HD2500	2GB	320GB	No OS
	E487570	Intel Core i3 3.3GHz HD2500	2GB	320GB	Windows 7
ECMG2-i5	E272400	Intel Core i5 3.6GHz HD4000	4GB	320GB	No OS
	E584199	Intel Core i5 3.6GHz HD4000	4GB	320GB	Windows 7
	E009007	Intel Core i5 3.6GHz HD4000	4GB	320GB	Windows 8.1

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America

Elo Touch Solutions
1033 McCarthy Boulevard
Milpitas, CA 95035

800-ELO-TOUCH

Tel +1 408 597 8000
Fax +1 408 597 8050
customerservice@elotouch.com

Europe

Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America

Tel 786-923-0251
Fax 305-931-0124
www.elotouch.com

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo) and Elo Touch Solutions are trademarks of Elo Touch Solutions, Inc. Copyright 2014 Elo Touch Solutions, Inc. All rights reserved. DS000079, rev B 08/2014

