

RECEIPT/LABEL



LOGISTICS



TRANSPORTATION



WAREHOUSE MANAGEMENT



HOSPITAL



DELIVERY



DRUGSTORE

RECEIPT



FOOD DELIVERY



RESTAURANT



BUS/TAXI RECEIPT



TRAFFIC CITATION

**Powerful and Easy to use,
2 inch Portable Printer**

LK-P12II

- Receipt/Label Printer
- Compact and rugged design
- High-speed printing : 127mm/sec
- Peel-off function(Optional)
- IP42 certified : protection against dust and water
- Large capacity of paper roll up to 56mm(OD)
- Adjustable paper width from 12.7 to 58mm
- Flexible connectivity including Serial(RS-232C), USB 2.0, Bluetooth Smart Ready(Bluetooth 4.2+BLE) or Wi-Fi(802.11 a/b/g/n)
- Fast AC charger and long life battery
- Memory : SDRAM 8 MB, Flash 16MB



PEELER

NON PEELER



SPECIFICATION

2 INCH PORTABLE PRINTER

LK-P12II

PRINTING SPECIFICATION

PRINTING

METHOD : Direct Thermal
SPEED : 127mm/sec
WIDTH : 48 mm
RESOLUTION : 203 DPI (8 dots/mm)

BARCODE

1D : EAN-8, EAN-13, EAN-128, Postnet, Code39, Code93, Code128, Codabar, ITF, UPC-A, UPC-E
2D : PDF417, QR Code, Maxicode, GS1 / DataBar™ (RSS) family, Datamatrix, Aztec

PAPER/MEDIA SPECIFICATION

PAPER

TYPE : Thermal receipt / label
WIDTH : 12.7~58mm
ROLL DIAMETER : Max. Ø 56mm

FONTS

INTERNAL FONT : Font A, Font B, Download bitmap and true type font

HARDWARE SPECIFICATION

MEMORY

SDRAM : 8MB/ FLASH : 16MB

BATTERY CHARGER

AC/DC Charger

BATTERY

7.4V / 2200mAh, 2600mAh

SENSOR

STARNDARD : Paper End, Gap, Black Mark, Cover Open

TEMPERATURE

OPERATING TEMPERATURE : -10 ~ 50 °C
STORAGE TEMPERATURE : -20 ~ 60 °C

HUMIDITY

OPERATING HUMIDITY : 10 ~ 90%
STORAGE HUMIDITY : 10 ~ 90%

DROP RESISTANCE

1.5M onto concrete

IP

IP42 certified

INTERFACE

INTERFACE

STANDARD : Serial(RS-232C), USB 2.0
OPTION : Bluetooth Smart Ready(Bluetooth 4.2+BLE), Wi-Fi(802.11 a/b/g/n)

SOFTWARE

EMULATION

ESC/POS, CPCL, ZPL Command compatible

DRIVER

DRIVER

Windows Driver(2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Window CE & Mobile Driver & SDK(CE 4.2~, Mobile 5.0~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1~) SDK, Blackberry SDK, Symbian

DIMENSION SPECIFICATION

DIMENSION

W x D x H(mm) : 100×158×85 (mm)
W x D x H(inch) : 3.93×6.22×3.34 (inch)

WEIGHT

580g (with battery)

OPTION

PEELER




PRODUCT FEATURES

CONTROL PANEL USAGE



- 1 MENU
- 2 PAPER FEED
- 3 LCD WINDOW
- 4 MENU SELECTION
- 5 POWER



J.STEPHEN Lab., Ltd.

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 447-210 Republic of Korea

TEL +82-31-8077-5000 FAX +82-31-459-8880

E-Mail : sales@miniprnter.com

