



Roteador TP-Link TL-WR841HP

Com o seu hardware atualizado, o TL-WR841HP supera facilmente os roteadores padrão, fornecendo cobertura sem fio consideravelmente expandida e conexões significativamente mais confiáveis.



300Mbps High Power Wireless N Router

Boosted Coverage,
Breaks Through Walls

TL-WR841HP



300Mbps



9dBi Antennas



Maximum Range

Highlights


Superior Coverage

An array of high-powered features provides wireless coverage for areas of up to 10,000 square feet.



Wall-Breaking Wi-Fi


The supercharged wireless signal cuts through walls and other physical barriers, eliminating dead zones for a worry-free Wi-Fi network.



Highlights


High-Gain Stability

Two 9dBi antennas make stable connections for reliable Wi-Fi to all your devices.



Tap into Multi-Mode

The RE Button lets you effortlessly switch between router and extender modes. Access point mode is also available from the web utility or Tether App.



Features



Reliability

- Wireless N Speed – 300Mbps Wi-Fi speed meets your daily internet needs
- 802.11n – Backward compatible with 802.11b/g products
- Easy Bandwidth Management– Bandwidth Control allocates necessary speed of each connected device to ensure quality of multimedia streaming



Ease of Use

- Intuitive Web UI – Ensures quick and simple Installation without hassle
- Fast Encryption – One-touch WPA wireless security encryption with the WPS button
- Hassle-free Management with Tether App – Network management is made easy with the TP-Link Tether App, available on any Android and iOS device




Security

- Guest Network – Keeps your main network secure by creating a separate network for friends and visitors
- Access Control – Establishes a whitelist or blacklist to allow or restrict certain devices to access the internet
- Parental Controls – Restricts internet access time and contents for children devices
- Encryptions for Secure Network – WPA-PSK and WPA2-PSK encryptions provide active protection against security threats

Specifications

Hardware

- Ethernet Ports: 4 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port
- Buttons: Power On/Off Button, Wi-Fi On/Off Button, Reset Button, WPS Button, RE Button
- Antennas: Two 9dBi Detachable Antennas
- External Power Supply: 12V/1A
- Dimensions (W x D x H): 9.0× 7.5×1.9 in. (228×190×48mm)



Wireless

- Wireless Standards: IEEE 802.11b/g/n
- Frequency: 2.4GHz
- Signal Rate: 300Mbps
- Transmit Power: CE: < 20dBm, FCC: <30dBm
- Reception Sensitivity:
2.4GHz:
270M: -71dBm@10% PER
130M: -74dBm@10% PER
108M: -74dBm@10% PER
54M: -77dBm@10% PER
11M: -94dBm@10% PER
6M: -93dBm@10% PER
1M: -97dBm@10% PER
- Wireless Function: Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
- Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions

Specifications

Software

- Quality of Service: WMM, Bandwidth Control
- WAN Type: Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)/BigPond
- Management: Access Control, Local Management, Remote Management
- DHCP: Server, DHCP Client List, Address Reservation
- Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
- Dynamic DNS: DynDns, NO-IP
- Access Control: Parental Controls, Local Management Control, Host List, White List, Black List
- Firewall Security: DoS, SPI Firewall, IP and MAC Address Binding
- Protocols: IPv4, IPv6
- Guest Network: 2.4GHz guest network

Others

- Certification:
CE, FCC, RoHS
- System Requirements:
Microsoft Windows 98SE/NT/2000/XP/Vista™/7/8/8.1/10, MAC OS, NetWare, UNIX or Linux

Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser
- Environment:
Operating Temperature: 0℃~40℃ (32°F ~104°F)
Storage Temperature: -40℃~70℃ (-40°F ~158°F)

Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
- Package Contents
High Power Wireless Router TL-WR841HP

Power Supply Unit

Ethernet Cable

Quick Installation Guide



For more information, please visit
<http://www.tp-link.com/en/products/details/TL-WR841HP.html>
or scan the QR code left

Attention: This device may only be used indoors in all EU member states and EFTA countries.
Specifications are subject to change without notice. TP-Link is a registered trademark of TP-Link Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. Copyright ©2017 TP-Link Technologies Co., Ltd. All rights reserved.

TP-Link Technologies Co., Ltd.
Building 24 (floors 1, 3, 4, 5) and 28 (floors 1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China
www.tp-link.com

www.tp-link.com

TP-Link 300Mbps High Power Wireless N Router TL-WR841HP