



## PinPad Verifone C680

Equipado com uma interface touchscreen, teclado iluminado e um processador poderoso para melhor desempenho e velocidade. Opções de conectividade versáteis tornam um dispositivo para todos os usos.





## Verifone C680

An affordable, versatile, portable payment device to support merchants on the go or at the counter—with flexible connectivity and use cases.

### PROCESSOR

400 MHz, ARM11 32-bit RISC

### MEMORY

192 MB (128 MB Flash, 64 MB SDRAM);  
TF memory card slot: up to 32 GB

### DISPLAY

3.5" (320 × 480) HVGA, TFT color LCD,  
resistive touchscreen, LED backlight

### PRINTER

25 lps, 40 mm paper roll

### OPERATING SYSTEM

Verix

### CONNECTIVITY

GPRS, 3G, and/or Bluetooth 4.0 + 2.4 GHz  
WiFi

### CARD READERS

Triple track MSR, smart card reader

### CONTACTLESS

ISO 14443 Types A and B, ISO 18092-  
capable, EMVCo L1 certification, MIFARE,  
supports major NFC/CTLS schemes

### PERIPHERAL PORTS

2 Micro-USB connectors: 1 host, 1 client;  
2 powered RS-232

### AUDIO

Buzzer

### BARCODE SCANNER

Optional integrated barcode scanner  
(GPRS variant)

### SECURITY

PCI PTS 4.X-approved

### POWER SUPPLY

Battery: 3.7 V/2450 mAh Li-Ion

PSU: 100-240 VAC w/ output DC 5 V, 2.2 amp

### ENVIRONMENTAL

Operating temperature: -10° to 50° C  
(14° to 122° F)

Storage temperature: -20° to 70° C  
(-4° to 158° F)

Relative humidity: 5% to 90%, non-condensing

### PHYSICAL

173 mm L × 82 mm W × 59 mm H; 352 g

### OTHER STANDARD FEATURES

2 SAM slots

### OPTIONAL EXTERNAL

#### COMMUNICATIONS DONGLE

Dial-up, Ethernet, powered RS-232, USB