



## Impressora Zebra 105SL Plus

A impressora industrial de etiquetas 105SL Plus é desenhada para se adequar com facilidade a operações já existentes. A impressora vem com várias opções de conectividade padrão, juntamente com compatibilidade total com modelos anteriores, tornando a integração rápida e simples.

# Zebra® 105SL™



## Serious About Bar Coding? Here's the Choice of Experience

The 105SL combines enhanced memory, processing capacity, and features with rugged and reliable all-metal construction. Proven platform longevity plus fast processing and print speed make it the choice of experienced users who value reliability, productivity, consistent print quality, network compatibility, and superior service and support.

## Cutting-Edge Network Connectivity

The 105SL offers flexible connectivity options including ZebraNet® Wireless Plus print server to free you to move or reconfigure the printer without costly recabling, plus ZebraNet 10/100 Print Server, which offers a complete wired solution when using 10Base-T, 100Base-TX, and fast Ethernet 10/100 auto-switching networks. And with Zebra advanced printer management, gain the efficiency and the ease of centralized monitoring and control of your Zebra printers and ZebraNet print servers.



The 105SL is ideal for moderate- to high-volume printing applications (including distributed, batch, or single format) in:

- Manufacturing and compliance labeling
- Logistics and inventory control
- Product identification marking
- Work in process

## GENUINE ZEBRA™ SUPPLIES

Get the most out of your resources—use genuine Zebra supplies! Our wide range of printer media and ribbons are Zebra-manufactured and -tested to ensure optimal performance in Zebra printers.

▶ For more information, visit [www.zebra.com](http://www.zebra.com)



# Specifications at a Glance\*

## Standard Features

- Print methods: Thermal transfer or direct thermal
- Construction: Steel frame and cabinet with metal interior components
- Single-level Element Energy Equalizer™ (E<sup>3</sup>™) for superior print quality
- Fast 32-bit processing
- Selectable print speeds up to 8"/second
- Transmissive media sensor
- Standard 2-line, 16-character LCD control panel
- Internal real-time clock
- Unicode™ compliant
- XML-Enabled printing—direct-connect integration for bar code label printing; eliminates license fees and print server hardware and lowers customization and programming costs

## Printer Specifications

### Resolution

- 203 dpi/8 dots per mm;
- 300 dpi/12 dots per mm (optional)

### Memory

- Standard: 6 MB SDRAM; 4 MB Flash
- Optional:
  - Up to 256 MB—PCMCIA card or CompactFlash® (CompactFlash not supported with ZebraNet Wireless Plus)
  - 64 MB Flash memory (factory installed)

### Print Width

- Width: 4.09"/104 mm
- Print Length with 203 dpi: 106"/2,692 mm (with standard memory)
- Print Length with 300 dpi (optional): 65"/1,651 mm (with standard memory)

### Print Speed

8"/203 mm per second (203/300 dpi)

### Media Sensors

Transmissive (standard) and Reflective (optional)

## Media Characteristics

### Maximum label and liner length

39"/991 mm

### Maximum label and liner width

.79"/20 mm to 4.52"/115 mm

### Maximum roll outer diameter (O.D.)

8"/203 mm

### Core inner diameter (I.D.)

3"/76 mm

### Media thickness

.003"/.076 mm to .012"/.305 mm

### Media types

Roll-feed, die-cut, continuous, fanfold, tags, tickets

## Ribbon Characteristics

### Outside diameter

3.2"/81.3 mm

### Standard length

984/300 m to 1,476/450 m

### Ratio

2:1 and 3:1 media roll to ribbon ratio

### Width

.79"/20 mm to 4.5"/114 mm

### Ribbon setup

- Ribbon wound ink side out
- Ribbon is recommended to be at least as wide as media.

### Core inner diameter (I.D.)

1"/25.4 mm

## Operating Characteristics

### Environmental

- Operating Temp. 32° F/0° C to 104° F/40° C
- Storage/Environ. -40° F/-40° C to 140° F/60° C
- Operating Humidity 20-85% non-condensing
- Storage Humidity 5-85% non-condensing

### Electrical

Universal power supply with factor correction  
90-264 VAC; 48-63 Hz

### Agency Approvals

UL 1950; CISPR 22 (Class B); CSA 950; IEC 950; 801-2, -3 and -4 standards; Canadian Doc. (Class A); FCC (Class A); CE compliance

## Physical Characteristics

- Width: 11.2"/283 mm
- Height: 15.5"/394 mm
- Depth: 19.5"/495 mm
- Weight: 55 lbs/25 kg
- Shipping weight: 63 lbs./29 kg

## Related Products

### Options and Accessories

- 300 dpi printhead
- Full width cutter with orderable catch tray
- Internal rewind spindle
- Peel/liner rewind (for print-and-apply)
- Reflective media sensor
- Fanfold bin

## Zebralink™ Solutions

### Software

- ZebraDesigner™ Pro
- ZebraDesigner for XML
- ZebraDesigner
- ZebraNet™ Bridge Enterprise
- ZebraNet Utilities v 7.0
- Zebra Universal Driver
- European and Asian font sets
- ZBI-Developer™

### Networking

- ZebraNet® 10/100 Print Server
- ZebraNet Wireless Plus
- Twinax and coax interfaces (internal)

### Firmware

- ZPL II®
- Global Printing
- APL-I™/APL-D™ (Contact Zebra Development Services for additional details)
- Web View
- Alert
- XML-Enabled printing
- ZBI 2.0™

## Communication and Interface Capabilities

Centronics® RS-232 RS-422\*, and RS-485\* serial ports;  
IEEE 1284 bi-directional parallel

## Bar Code Symbolologies

### Linear Bar Codes

Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case Codes, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2 or 5 digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar, GS1 DataBar (RSS)

### 2-Dimensional

Codablock, PDF417, Code 49, Data Matrix, MaxiCode, QR Code, MicroPDF417, GS1 DataBar (RSS), Aztec

## Fonts and Graphics

### Fonts and Character Sets

- Standard Fonts: 7 bitmapped, 1 smooth scalable (CG Triumvirate™ Bold Condensed)
- Sets: IBM® Code Page 850 International character set
- Contains UFST® from Monotype Imaging, Inc.

### Graphic Features

- Supports user-defined fonts and graphics—including custom logos
- ZPL II drawing commands—including boxes, circles and diagonal lines

For optimum print quality and printer performance, use genuine Zebra™ supplies.

\*Specifications subject to change without notice.

©2010 ZIH Corp. ZebraDesigner, ZebraLink, ZebraNet, ZBI 2.0, ZBI-Developer, APL, Element Energy Equalizer, E<sup>3</sup>, and all product names and numbers are Zebra trademarks and Zebra, the Zebra head graphic, ZebraNet, and ZPL II are registered trademarks of ZIH Corp. All rights reserved. Centronics is a registered trademark of Centronics Data Computer Corporation. CG Triumvirate and UFST are trademarks of Monotype Imaging, Inc. and may be registered in certain jurisdictions. IBM is a trademark or registered trademark of International Business Machines Corporation in the United States, other countries, or both. CompactFlash is a registered trademark of SanDisk Corporation. Unicode is a trademark of Unicode, Inc. All other trademarks are the property of their respective owners.



www.zebra.com

### Corporate Headquarters

+1 800 423 0442

E-mail: inquiry4@zebra.com

### Asia-Pacific Headquarters

+65 6858 0722

E-mail: apacchannelmarketing@zebra.com

### EMEA Headquarters

+44 (0)1494 472872

E-mail: mseurope@zebra.com

### Latin America Headquarters

+1 847 955 2283

E-mail: inquiry4@zebra.com

### Other Locations

**USA:** California, Georgia, Rhode Island, Texas, Wisconsin **Europe:** France, Germany, Italy, Netherlands, Poland, Spain, Sweden **Asia Pacific:** Australia, China, India, Japan, South Korea **Latin America:** Argentina, Brazil, Florida (USA), Mexico **Africa/Middle East:** Russia, South Africa, United Arab Emirates

GSA#: GS-35F-0268N  
P1024472 Rev. 28 (12/10)